

text for tenders

cubicle system made of glass
astec s.200

cubicle system made of glass with stainless steel fittings for cubicles in sanitary, shower or changing room areas.

manufacturer: astec gmbh, design fittings (www.astec-design.de)

cubicle system consisting of frameless glass panels made of laminated safety glass (lsg). dividing walls and front doors are directly connected with wall or floor via stainless steel clamping fittings. dividing wall protrudes beyond the door front by approximately 100 mm cubicles are mounted with small separating joints without any additional sealing ledge.

dimensions:

standard height: 2150 mm, floor clearance approx. 35 mm,
depth of dividing wall and width of door are according to architectural specifications.
door width is in accordance with width of cubicle, recommended dimension approx. 900 mm, the offset pivot point of fitting towards the inside of the cubicle allows free passage width through door, according to door width minus approx. 150 mm.

glass:

laminated safety glass approximately 11 mm consisting of two tempered glass panels.
tolerance from planarity: not more than 3 mm related to 2000 mm length:
glass colour respectively design of glass surface according to customers choice. all glass edges chamfered and polished all around.

fittings:

stainless steel fittings in solid design. (1.4305). visible surfaces finely ground and brushed matt. the retaining fittings and the door fittings are solely clamped. door lock and door latch are mounted into glass drillings.

fitting set 1: for door opening towards the inside.

fitting set 2: for door opening towards the outside.

system includes:

1 pce dividing wall lsg approx. 11 mm, length and height are according to architectural specification, with fixing hole for door latch

1 pce door panel lsg approx. 11 mm, width and height are according to architectural specification, with fixing hole for door lock

fitting set includes floor pivot with clamping bracket, wall fitting with clamping bracket, floor pivot with clamping bracket, top door fitting with clamping bracket and connecting clamping at stabilization bar, stabilization bar with wall connection rosettes, complete door lock.

pos.nr.	description	qty.	Single price	total
.....	dividing wall system acc. to building plan	1
	accessories			
.....	wc roll holder, stainless steel for glass-/wall mounting
.....	spare wc roll holder, stainless steel Ø 25 x 108 mm for glass-/wall mounting
.....	wc brush set, stainless steel for glass-/wall mounting
.....	wc coat hook, stainless steel for glass-/wall mounting
.....	urinal dividing walls
.....	top door-fitting with self closing function (replaces standard top door-fitting)