

text for tenders

stainless steel sliding door fitting
astec b.900

stainless steel sliding door fitting on show with flattened carrying rod and polyamide rollers, for glass or wooden door leaves. suitable for wall fixing or for fixing in allglass systems.all visible surfaces are finely processed and brushed matt.

manufacturer: astec gmbh, design fittings (www.astec-design.de)

system includes:

2 pcs hangers with polyamide rollers, 59 mm diameter. support beam in tender, bended shape. bolted-connections of the support beam to the doorleaf and roller-connections are designed invisibly.

1 pce carrying rod, all solid stainless steel. flattened profile 26 mm x 22 mm with guiding radius for the rollers at the upper side and a receiving slot for the door stopper/anti-liftout components at the opposite side.

2 pcs doorstoppers, continously adjustable, fitted invisibly at the support beam of the hangers and guided in the receiving slot of the carrying rod. doorstopper and anti-liftout function integrated in one single unit.

number and position of wall or glass fitting components according to the individual length of the carrying rod. connections are designed invisibly.

1 pce floor guide for door leaf:

for glass door leaves 10/12mm: u-shaped profile, solid stainless steel,

for wooden door leaves: T-profile guiding blade made of polyamide,

with all fixing components, complete documentation,

from the astec accessories range are also available:

astec pull handles

astec knobs

astec recessed grips

astec locks